# CONTOUR





#PSSCONTC13

#PSSCONTP11

# MICROFIBER POUCH INCLUDED

#PSSCONTO64



#PSSCONT443

PLATINUM® (†P) ASAF Coating
Permanent coating on both sides of the lens gives them a high
resistance to scratching, and delays the onset of fogging. Certified
K & N (EN166) PLATINUM® resists to the most aggressive chemicals.

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments. CSP is also combined with the exclusive PLATINUM® coating that sustainably combats fogging.

# **POLARIZED**

A technology approved for permanent wear and certified with perfect optical quality, it offers unbeatable comfort by filtering glare and reflections. Ideal for the maritime environment. Filters 99.99% of UVA/UVB.



# CONTOUR



MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	V50 BALISTIC RESISTANCE STANAG 2920	ANSI/MIL	COATINGS
CONTOUR	Clear	PSSCONT064	2C-1.2 😭 1 FT KN C€	≌ EN166 FT C€	=	ANSI Z87.1	Anti-scratch/anti-fog
	Smoke	PSSCONT443	5-2,5 😭 1 FT KN C€	≅ EN166 FT C€	-	ANSI Z87.1	Anti-scratch/anti-fog 🔁
CONTOUR	CSP	PSSCONTC13	5-1,4 😭 1 FT KN C€	≅ EN166 FT C€	-	ANSI Z87.1	Anti-scratch/anti-fog
	POLARIZED	PSSCONTP11	5-3,1 😭 1 FT C€	≅ EN166 FT C€	-	ANSI Z87.1	Anti-scratch

# Lens markings

## Optical class symbols:

1. Continuous work

# Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

## Others symbols:

K. Resistance to surface damage by fine particles

N. Resistance to fogging

Bollé Safety product approval certificates to CE standards will be sent on request.

# Frame markings

EN166. guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

## Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

### Others symbols:

	PSSCONT064	PSSCONT443	PSSCONTC13	PSSCONTP11
EAN13 Unit pack	3660740010942	3660740010959	3660740010966	3660740011635
EAN13 Inner pack	3660740110949	3660740110956	3660740110963	3660740111632
(number of unit per inner pack)	(10 units)	(10 units)	(10 units)	(10 units)
Size // Weight	24x18x9 cm	24x18x9 cm	24x18x9 cm	24x18x9 cm
Inner pack	0.51 kg	0.51 kg	0.51 kg	0.51 kg
EAN13 Carton	3660740210946	3660740210953	3660740210960	3660740211639
(number of unit per master pack)	(240 units)	(240units)	(240units)	(240 units)
Size // Weight	60x50x37 cm	60x50x37 cm	60x50x37 cm	60x50x37 cm
Master pack	13.4 kg	13.4 kg	13.4 kg	13.4 kg

Maintenance: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

Storage: All product	's must be stored	in a dry and	clean environment.
----------------------	-------------------	--------------	--------------------

CONTOUR				
LENSES	PC - 2.2 mm - Curve 8			
FRAME	PC			
TEMPLES	Nylon + TPE			
STRAP	Not applicable			
FOAM	Not applicable			
Country of origin	Taiwan			















For more information on this product and the BSSI range, visit:

www.bollesafety-si.com

**BOLLÉ SAFETY** 34 rue de la Soie 69100, Villeurbanne **FRANCE**