

RUSH+



FRAME
 + UPPER PROTECTION
 + NON-SLIP NOSE BRIDGE
 + SINGLE-LENS FRAME

TEMPLES
 + BI-MATERIAL TEMPLES FOR MORE COMFORT
 + FOAM AND STRAP KIT (OPTION)

LENS
 + PLATINUM® ASAF COATING
 + PANORAMIC FIELD OF VISION

VERSIONS



CLEAR
 #PSSRUSP064



SMOKE
 #PSSRUSP443



CSP
 #PSSRUSPC13



TWILIGHT
 #PSSRUSPT09



STRAP & FOAM
 #RUSHKITFS



+ MICROFIBER POUCH INCLUDED

DESCRIPTION

Sporty, RUSH+ provides a panoramic field of vision and offers an attractive design thanks to its flexible co-injected temples. Also ultra-light, RUSH+ ensures perfect optical quality and ultimate comfort.

PLATINUM® (+P) ASAF Coating

Permanent coating on both sides of the lens gives them a high resistance to scratching, and delays the onset of fogging. Certified K & N (EN166) PLATINUM® resists to the most aggressive chemicals.

CSP











This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments.

TWILIGHT

The TWILIGHT technology offers the advantages of ESP and more. Designed and used in low light conditions, it improves contrast. Its light transmission rate is perfect for outdoors, particularly early morning and late evening. TWILIGHT filters 76% of blue light.

TECHNOLOGIES



MODEL	FRAME	VERSIONS	REFERENCES	LENS MARKINGS	FRAME MARKINGS	V50 BALISTIC RESISTANCE STANAG 2920	ANSI/MIL	COATING
RUSH+	■ Black	 Clear	PSSRUSP064	2C-1.2  1 FT KN C€	 EN166 FT C€	-	ANSI Z87.1 MIL-PRF-32432A	ASAF 
	■ Black	 Smoke	PSSRUSP443	5-3.1  1 FT KN C€	 EN166 FT C€	-	ANSI Z87.1 MIL-PRF-32432A	ASAF 
	■ Black	 CSP	PSSRUSPC13	5-1.4  1 FT KN C€	 EN166 FT C€	-	ANSI Z87.1 MIL-PRF-32432A	ASAF 
	■ Black	 Twilight	PSSRUSPT09	5-2  1 FT KN C€	 EN166 FT C€	-	ANSI Z87.1 MIL-PRF-32432A	ASAF 
	Foam & Strap Kit	-	RUSHKITFS	-	-	-	-	-

Lens markings

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles

N. Resistance to fogging

C€ European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

Frame markings

Standards :

EN166. guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

C€ European standard  Manufacturer name

	PSSRUSP064	PSSRUSP443	PSSRUSPC13	PSSRUSPT09	RUSHKITFS
EAN13 Unit pack	3660740010751	3660740010768	3660740010775	3660740010782	3660740006488
EAN13 Inner pack (number of unit per inner pack)	3660740110758 (10 units)	3660740110765 (10 units)	3660740110772 (10 units)	3660740110789 (10 units)	3660740106485 (20 units)
Size // Weight Inner pack	24x18x9 cm 0.6 kg	24x18x9 cm 0.6 kg	24x18x9 cm 0.6 kg	24x18x9 cm 0.6 kg	28x16x7 cm 0.3 kg
EAN13 Carton (number of unit per master pack)	3660740210755 (200 units)	3660740210762 (200 units)	3660740210779 (200 units)	3660740210786 (200 units)	3660740206482 (240 units)
Size // Weight Master pack	60x50x37 cm 13.6 kg	60x50x37 cm 13.6 kg	60x50x37 cm 13.6 kg	60x50x37 cm 13.6 kg	46x37x28 cm 4.7 kg

Maintenance: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

Storage: All products must be stored in a dry and clean environment.

RUSH+	
Lens	PC - 2.3 mm - Curve 9
Temples	PC + TPR
Strap	Nylon - 15mm
Foam	SBR + Nylon
Spare lens	No
Country of Origin	Taiwan



For more information on this product and the BSSI range, visit:

www.bollesafety-si.com

BOLLÉ SAFETY

34 rue de la Soie

69100, Villeurbanne

FRANCE